

MARDI GRAS TECHNICAL SPECIFICATIONS

Mardi Gras is semi-aniline, pebbled grain leather with a tipped, two-tone, semi-shine finish. As a Leathershield product, it offers excellent durability for heavy, medium traffic areas with minimal maintenance.



CTL LEATHER
A Garrett Leather Company

PROPERTY	TEST METHOD	RESULT
Average Hide Size		50 FT2
Average Thickness	UNI ISO 2589	0.9 - 1.1 mm
Tensile Strength	UNI ISO 3376	> 6 N/mm2
Elongation at Break	UNI ISO 3376	Min. 30% - Max. 60%
Tear Strength	UNI ISO 3377	>40 N/mm
Flexing Endurance 20,000 cycles	UNI EN ISO 5402	20000 No Damage
Color Fastness to Artificial Light (Xenotest 72 Hrs.)	ISO 105 B 02	2 (Blue Scale)
Color Fastness to Rubbing (100 Dry Rubs, 50 Wet Rubs)	ISO 11640, ISO 11640	4, 4
Finishing Adhesion	ISO 11644	>3 N/cm
Determination of pH	ISO 4050	OK - min 3, se pH <4, pH <0.7
Ignitability BS 5852-1 (Cigarette)	BS 5852:1 EN 1021:1	Pass
Ignitability BS 5852-2 (Match)	BS 5852:2 EN 1021:2	Pass
California Technical Bulletin 117	Cal Tech Bulletin 117-2013	Pass
Cigarette Ignition Resistance	UFAC/NFPA 260	Class 1
Boston Fire Dept	BFD IX-I	Pass
Wyzenbeek - (Oscillatory Cylinder Method) @ 3,000 cycles	ASTM D 4157.13	Pass