

PARADISO TECHNICAL SPECIFICATIONS

Paradiso is leather with microfiber on top, soft microfiber leather with a matte finish. As a Leathershield product, it offers excellent durability for heavy traffic areas with minimal maintenance.



PROPERTY	TEST METHOD	RESULT
Average Hide Size		25-30 FT2
Average Thickness	UNI EN ISO 2589 : 2006	1.2 - 1.4
Tear Strength (single edge tear)	UNI EN ISO 3377-1 : 2006	57
Tear Strength (back bone direction)	UNI EN ISO 3377-1 : 2006	70
Tear Strength (perpendicular to back bone direction)	UNI EN ISO 3377-1 : 2006	43
Flexing Endurance (50,000 cycles)	UNI EN ISO 5402 : 2004	≥ 50,000 cycles
Color Fastness to Artificial Light	UN EN ISO 105 B02 : 2004	≥ 4 Blue Scale
Color Fastness to Rubbing (Dry, 500 Rubs)	UNI EN ISO 11640 : 2000	3 - 4 Grey Scale
Color Fastness to Rubbing - Staining (Dry, 500 Rubs)	UNI EN ISO 11640 : 2000	4 - 5 Grey Scale
Color Fastness to Rubbing (Wet, 250 Rubs)	UNI EN ISO 11640 : 2000	3 - 4 Grey Scale
Color Fastness to Rubbing - Staining (Wet, 250 Rubs)	UNI EN ISO 11640 : 2000	4 - 5 Grey Scale
Color Fastness to Rubbing (Perspiration, 80 Rubs)	UNI EN ISO 11640 : 2000	3 - 4 Grey Scale
Color Fastness to Rubbing - Staining (Perspiration, 80 Rubs)	UNI EN ISO 11640 : 2000	4 - 5 Grey Scale
Abrasion Resistance	UNI EN ISO 12947-2 : 2000	≥ 40,000
Finishing Adhesion	UNI EN ISO 11640 : 2009	5 N/cm
Determination of pH	UNI EN ISO 4045 : 2008	4.8
Ignitability BS 5852-0 (Cigarette)	BS 5852:1979	Pass
Ignitability BS 5852-1 (Match)	BS EN 1021-1-2 : 2006	Pass
Pilling Test (5,000 cycles)	UNI EN ISO 12945-2 : 2002	≥ 4/5
Seam Slippage (3mm)	UNI EN ISO 13936-1 : 2004	≥ 200